



# High Speed POS Printer

## RP-300-H



The RP-300H is an extremely fast and powerful thermalbond printer with up to 200 mm/s printing speed and a resolution of 180 dpi. With its compact size and integrated wall-mounting feature, the durable model is perfect for use in various application areas. A variety of interface possibilities allow for the easy connection of the printer to an existing cash register system. The thermal paper roll prints cost effectively until the end. And the best thing is that thanks to singular, one-of-a-kind technology the RP-300H with 8MB of logo memory also simultaneously (approved by) prints coupons, promotional texts, rebate offers or other customer information.

### **Special Features:**

- ➔ Resolution 180 dpi
- ➔ Integrated wall mounting
- ➔ Signal tone remote
- ➔ Available in black and light grey
- ➔ Interface options: RS232, USB, parallel, LAN, WL AN
- ➔ Auto cutter
- ➔ Power unit included

## High Speed POS Printer RP-300-H

### Technical specifications

<b>Print method</b>	Direct Thermal
<b>Printing speed</b>	200 mm/sec.
<b>Dot density</b>	180 x 180 DPI
<b>Dot pitch</b>	0,141 x 0,141 mm
<b>Effective printing width</b>	72 mm, 512 Dots/lines
<b>Printing direction</b>	Unidirectional with friction feed
<b>Character per line</b>	Font A (12 x 24) 42 columns Font B (9 x 17) 56 columns
<b>Paper Type:</b>	Thermal paper
<b>Width:</b>	50 mm - 82,5 mm
<b>Thickness:</b>	0,06 - 0,09 mm
<b>Rolldiameter:</b>	max. Ø 83 mm
<b>Roll core inner:</b>	12,5mm +/- 0,5 mm
<b>Reliability TPH:</b>	100 km
<b>MCBF:</b>	60,000,000 Lines
<b>Character set</b>	95
<b>Alphanumeric:</b>	128 x 18 page (1 space page)
<b>Extended graphic:</b>	14
<b>International:</b>	
<b>Barcode</b>	EAN-8, EAN-13, CODE39, ITF, UPC-A, CODABAR, CODE93, CODE128, PDF417(2D)
<b>Emulation</b>	ESC/POS Command compatible TMT-88III
<b>Driver</b>	Epson driver compatible
<b>Sensor</b>	Papier end sensor, Cover open sensor, Black mark sensor (option), Paper low sensor (option)
<b>Cash drawer driver</b>	2 circuits (24V, 1A)
<b>Interface</b>	Serial RS-232C, Parallel (IEEE-1284), USB, Ethernet, Wifi, USB Combo
<b>Power</b>	100 - 240 V / 24 V 2,5 A
<b>Dimension</b>	152 (W) x 204 (D) x 150 (H) mm
<b>Weight</b>	1,7 Kg incl. auto cutter
<b>Option</b>	Water spill proof cover



### Partner Tech Taiwan

Tel: +886-2-29188500  
Fax: +886-2-29153405  
E-mail: sales@partner.com.tw  
Address: 10F, 233-2, Pao Chiao Road,  
Hsin Tien, Taipei, Taiwan, R.O.C

### Partner Tech USA

Tel: +1-949-598-1888  
Fax: +1-949-598-0088  
E-mail: sales@partnertechcorp.com  
Address: 51 Parker Irvine, CA 92618

### Partner Tech Europe

Tel: +49 (0)40 450 635-0  
Fax: +49 (0)40 450 635-130  
E-mail: info@partner-tech.eu  
Address: Fasanenweg 25,D-22145  
Hamburg,,Germany